Form 9-331 (May 1963)	DEPARTMEN OF T	ATES SUBMI HE INTERIOR Verse s	T IN TRIPLIC . Instructions 6 and ide)	Ford approve Budget Bureau 5. LEASE DENIGRATION A NM-0331649 a	SF d. u. No. 42-R1424. AND SERIAL NO.
SUNE (Do not use this for	DRY NOTICES AND orm for proposals to drill or to Use "APPLICATION FOR PERM	deepen or pite b ck to I diffe	Frent reservoir.	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
1. OIL GAS WELL VELL		APR 26		7. UNIT AGREEMENT NAM	(E
3. ADDRESS OF OPERATOR	on Company 🗸	APR 20 U.S. BEULUUUIT ARTESIA, NE	W MEXICO	8. FARM OR LEASE NAME Midwest "L" Fe 9. well no.	
 P.O. Drawer A. 4. LOCATION OF WELL (Re See also space 17 below At surface 	Levelland, Texas 7 port location clearly and in accord	JJJU	nents.*	1 10. FIELD AND FOOL, OR South Carlsbad	
1980' FSL X 19	980' FWL, Sec. 34, (Unit K NE/4 SW/4)	APR 28 1	11. BEC., T., B., M., OR BL SUBVEY OR ABEA	
14. PERMIT NO.	15. ELEVATIONS (3310.50	Show whether DF, RT, GR, etc.)		9784-22-26 12. COUNTY OR PARISH Eddy	13. state NM
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Office Data					
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	OMPLETED OPERATIONS (Clearly s rell is directionally drilled, give	E FRACTO SHOOT (Other	SHUT-OFF TRE TREATMENT ING OR ACIDIZING <u>COMPLETION</u> NOTE: Report results of Completion or Recomple	of multiple completion or	a Well
Moved in serv Loaded tbg an l½ minutes bu circulation o show of gas.	ice unit 1-30-78. P d casing annulus an t did not circulate ut annulus. Pulled Installed BOP. Pu	ulled tbg and pac d pressure to 250 . Pulled bridge p tbg and packer. lled tbg.	ker. Ran and s O#. Pressure 1 lug and pumpec Circulated ho	set bridge plug leaked off to 4 d down tbg. Ha ble clean and h	at 10988'. 00# in d full ad slight
Ran tbg and pkr and retreivable BP set at 11020'. Tested tbg to 5000#. Raised pkr to 10957'. Tested BP to 5000#, OK. Found leak in 4½" casing between 10523' X 10555'. Circulated 4½" casing and 9 5/8" casing annulus and recovered 20 bbl condensate, 40 bbl cut mud and 164 bbl salt water.					
Pull tbg and lite wate and top of cement	packer. Set CIBP a 200sx Cīass H ceme at 7350'.	t 10420'. Squeezo nt. Reversed out	e zone 10523' 15sx cement.	- 10555' w/550 Temperature su	sx trinity rvey shows
tog and set d	" casing w/2 JSPF a own in retainer. P 100sx Class H. Rev	umped down tha w/9	550sx Class H.	followed with	
					•
SIGNED Lavid	foregoing is true and correct	TITLE ASST. Admini	strative Anal	yst _{Dare} _April 2	25, 1978
(This space for Federal APPROVED BY CONDITIONS OF APPF 0 + 4 USGS-/ 1 - Div.	C. J. Lala SOVAL, IF ANY:	TITLE ACTING DISTR	ICT ENGINEER	DATE APR	2 7 1978
1 - Susp 1 - RC	*Se	e Instructions on Reverse	Side		