

(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

(Other instructions on reverse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

660' Fnl & 1980' FWL, Section 10, 21-S, 27-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3217' GL

5. LEASE DESIGNATION

NM-14768

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cerf-Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 10, 21-S, 27-E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Reached total depth of 12-1/4" hole at 2993' at 2:40 PM, April 10, 1973. Ran 93 joints and 1 cut joint, 2975' of 9-5/8" OD 36# K-55 ST&C Casing set and cemented at 2992' with 1000 sacks of Class C with 4% gel and 12-1/2#/sack of Gilsonite and 200 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC 24 hours. Tested casing with 2000#, 30 minutes, OK.

Started drilling 8-3/4" hole at 2993' at 4:00 AM, April 12, 1973

18. I hereby certify that the foregoing is true and correct

SIGNED

*H. J. Beazale*

TITLE Area Engineer

DATE April 12, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED  
APR 12 1973  
H. J. BECKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side