

C/SF

NM OIL CONS. COMMISSION

Drawer DD

Albuquerque, NM 88210

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Estoril Producing Corporation ✓
3. ADDRESS OF OPERATOR  
11th Floor, Vaughn Bldg., Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FWL  
AT TOP PROD. INTERVAL: 11,067'  
AT TOTAL DEPTH: 11,340'
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒



5. LEASE  
NM 17098
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Shell Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Winchester Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 1, T20S, R28E
12. COUNTY OR PARISH  
Eddy
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3272 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 4-1-83 Plug #1, 10,685'-10,490', 4½" CIBP, cemented w/14 sacks Class "C" cement.  
4-6-83 Plug #2, 9050'-8875' cemented w/40 sacks Class "C" cement.  
4-7-83 Plug #3, 4940'-4860' cemented w/35 sacks Class "C" cement.  
4-7-83 Plug #4, 2930'-3120' cemented w/40 sacks Class "C" cement.  
4-8-83 Plug #5, 3120'-2915' cemented w/125 sacks Class "C" cement.  
4-8-83 Plug #6, 2915'-2830' cemented w/100 sacks Class "C" cement.  
4-9-83 Plug #7, 348'-243', cemented w/40 sacks Class "C" cement.  
4-9-83 Plug #8, 50'-surface, cemented w/20 sacks Class "C" cement.

This well is now Plugged & Abandoned.

Post ID-2  
10-7-83  
P+H

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Production Clerk DATE 4-18-83

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL IF ANY

OCT 3 1983



\*See Instructions on Reverse Side