

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 067145

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Active Drilling Well	UNIT AGREEMENT NAME Big Eddy Unit
2. NAME OF OPERATOR Perry R. Bass	8. FARM OR LEASE NAME Big Eddy Unit
3. ADDRESS OF OPERATOR Box 1178, Monahans, Texas 79756	9. WELL NO. 36
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 660' FEL of Section 12, T21S, R28E.	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12, T21S, R28E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3356' Gr.	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Intermediate Casing Setting X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Drilled 11" hole to 2976' - finished at 1:00 AM MDT 6-7-73.

Ran 61 jts 8 5/8" 24#/ft, K-55, ST&C and 17 jts 8 5/8" 28#/ft, H-40, ST&C casing plus float collar and float shoe. Set at 2981.60'. Bottom 3 jts sand blasted and one (1) Gist positive centralizer per joint. Circulated 1 3/4 hours to condition hole. Cemented with 1125 sks Class "C" containing 24 1/2% salt per sack and 1% CaCl at 14.7 PPG followed by 250 sks Class "C" with 2 3/4% CaCl at 14.0 PPG. Mixed cement in 108 min. - displaced wiper plug in 22 min. at maximum pressure of 1000 psi. Pressured plug to 1500 psi. Circulated out 150 sks. Plug down at 4:08 PM MDT. WOC. Tested BOP to 5000 psi and Hydril to 3500 psi - held OK. Commenced drilling 7 7/8" hole at 6:00 PM, 6-8-73. Tested casing to 1500 psi prior to commencing drilling new hole.

RECEIVED
JUN 12 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Murty, Jr.

TITLE Division Production Clerk

DATE June 11, 1973

(This space for Federal or State office use)

APPROVED BY

Jan Li Xue

TITLE

DISTRICT ENGINEER

DATE

JUN 12 1973

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below; between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.