

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Plug and abandonment.	5. LEASE DESIGNATION AND SERIAL NO. LC 067145
2. NAME OF OPERATOR Perry R. Bass	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 1178, Monahans, Texas 79756	7. UNIT AGREEMENT NAME Big Eddy Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 660' FEL of Sec. 12, T21S, R28E.	8. FARM OR LEASE NAME Big Eddy Unit
14. PERMIT NO.	9. WELL NO. 36
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3356.5 Gr. 3373 KDB	10. FIELD AND POOL, OR WILDCAT Wildcat
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12, T21S, R28E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

Plug #1: 34 sks C1 H with 4/10% HR-4, 15.2 PPG, 11832' - 11732'.
Plug #2: 33 sks C1 H with 4/10% HR-4, 15.3 PPG, 10122' - 10022'.
Plug #3: 36 sks C1 H, 15.3 PPG, 8360' - 8260'.
Plug #4: 35 sks C1 H, 15.2 PPG, 6600' - 6500'.
Plug #5: 48 sks C1 H, 15.2 PPG, 4815' - 4715'.
Plug #6: 36 sks C1 H, 15.4 PPG, 3031' - 2931'. Plug #6 down at 9:35 AM, MDT, 7-18-73.

10.3 PPG mud between plugs.

Salvaged well head. Spotted 13 sks C1 H cement at 40' extending to surface. Installed regulation surface marker. Well P & A 7-25-73.

See reverse side for formation markers.

RECEIVED

AUG 20 1973

U.S. GEOLOGICAL SURVEY
EDDY, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H. B. Murty, Jr.

TITLE Division Production Clerk

DATE August 17, 1973

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUN 11 1974
K. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Elevations: 3373' KDB. 3356.5 GL. U.S. GOVERNMENT PRINTING OFFICE: 1953-O-685229

8-67-081

Formation Markers:

First Delaware Sand	3017 (+356)
Top Bone Spring	6547 (-3174)
First Bone Spring Sand	7584 (-4211)
2nd Bone Spring Sand	8362 (-4989)
Base Sand	8695 (-5322)
T/3rd Bone Spring Sand	9412 (-6039)
T/Wolfcamp Isopach	10072 (-6699)
T/Morrow	11782 (-8409)