

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI  
(Other instruction  
on reverse side)

ATE\*

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0558014

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harris-Bell

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Golden Lane Field

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 5-21S-29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Meadco Properties, Ltd.

3. ADDRESS OF OPERATOR

407 West Wall St., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)At surface 1980' FNL & 1880' FWL Section 5, T-21-S,  
R-29-E, Unit F

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3455 Gr

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running 13-3/8" casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded in 17-1/2" hole 7/3/73.

Drilled 17-1/2" hole to 617'. Ran 16 jts. 13-3/8" 54# casing to 617' RTM. Cemented with 500 sacks Halliburton Lite with 5# gilsonite, 1/4# Flocele and 2% calcium chloride per sack. Followed by 150 sacks Class C cement with 1/4# Flocele and 2% calcium Chloride per sack. Circulated approximately 75 sacks cement. Plug down 7:15 p.m. 7/4/73.

WOC 24 hrs.

Tested casing with 1,000# for 30 minutes. Tested okay.

Started drilling ahead in 12-1/4" hole.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Bill C. Carter*

TITLE Agent

DATE

7/6/73

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

*John A. Brown*

TITLE

DISTRICT ENGINEER

DATE

JUL 20 1973