

5 1/2" Liner

20# Hydril

13792'
w/top at
10866' in
BOP liner
hanger.

6 3/4"

410 sx Class H w/ 3/4" CFR-2 and 8# salt/sx.
Reversed out 100 sx.

8-29-73, Ran Howco double grip csg bowl on 129
jts. 7 5/8" csg, latched on to 7 5/8" csg at 5502,
and pulled to 220,000#, set csg slips (csg bowl
set 5502-06'). Csg rerun as follows: (bottom to top)
14 jts. (608') 26.4# S-95 Hydril SFPJ
113 jts. (4814') 26.4# N-80 Hydril triple seal
2 jts. (80') 29.7# N-80 Hydril triple seal
Nipped up csg.
8-30-73, Howco tested csg & blind rams w/2500# for
1/2 hr., OK, tested BOP & choke liner w/5000# and
Hydril w/2500# in 12 hrs.
8-31-73, Cleaned hole w/magnetic basket, tested
Hydril to 2500# & pipe rams to 5000#, ok. Drld cnt
and float 11234' to 11284' tested w/1000# ok. Drld.
cnt & shoe. Tested w/600#, OK. Started drlg ahead
at 11294 w/ 6 3/4" bit.

RECEIVED
NOV 19 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO