

PHILLIPS PETROLEUM COMPANY

James-C No. 1
35, 21-S, 30-E,
Eddy County.

Form 9-330,
Attachment No. 1

ITEM 28 - CASING RECORD.

Casing Size	Wt. lb/ft	Depth Set	Hole Size	Cementing Record	Amount Pulled
Conductor: 24"	_____	35'	30"	Ready mix cement to bottom of cellar.	_____
16"	65#	402'	20"	350 sx Trinity LW w/2% CaCl ₂ and 1/4# Flocele w/6# Gilsomite/sx plus 300 sx Class H w/270 CaCl ₂ . Circ 300 sx cement.	_____
10-3/4"	45.5#	3638'	13-3/8"	Cmtd w/2650 sx Trinity LW w/2% CaCl ₂ , 21# salt and 1/4# Flocele/sx followed by 300 sx Class C cmt w/2% CaCl ₂ and 19.6# salt/sx. Circ 500 sx cmt.	_____
7-7/8"	26.4#, 29.7#	11294'	9-1/2"	Howco cemented w/300 sx Class H w/ 3/10% LWL, 1% DA. Plug to 11250" w/527 BM, max press 900#, bumped w/1350#. Csg did not rotate. Job completed 8-23-73 WOC 24 hrs. ran West Engineering temp survey, TOC at 9480. On 8-25-73, Howco attempted to test casing, lines & BOP equipment; Ran PKR, tested, found casing parted at 5480: 8-26-73, Pulled and laid down 7 5/8" csg as follows: 2 jts. (80') 29.7# N-80, Hydril triple seal. 114 jts. (4814') 26.4# N-80 Hydril triple seal. 14 jts. (586') 26.4# S-95 Hydril SFP Top of 7 5/8" csg in hole at 5480. 8-27-73, Ran csg cutter, cut 7 5/8" csg at 5502' pulled 1 jt. (21.88') 26.4# S-95 Hydril SFP csg, left top of 7 5/8" csg, in hole at 5502'. 8-28-73, Dressed 7 5/8" csg cut at 5502'.	_____

RECEIVED
NOV 19 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO