

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

**RECEIVED**

SEP 13 1973

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	L-3568

**SUNDRY NOTICES AND REPORTS ON WELLS C. C.**  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PURPOSES.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Burton Flat Deep Unit
2. Name of Operator MONSANTO COMPANY	8. Farm or Lease Name Burton Flat (Deep) Unit
3. Address of Operator 101 North Marienfeld, Midland, Texas 79701	9. Well No. 5
4. Location of Well UNIT LETTER <u>V</u> , <u>1980</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>2</u> TOWNSHIP <u>21S</u> RANGE <u>27E</u> N.M.P.M.	10. Field and Pool, or Wildcat Und. Burton Flat-Morrow
15. Elevation (Show whether DF, RT, GR, etc.) DF 3239'; Gr. 3225'	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8 3/4" hole to Total depth 11,725' and set 5 1/2" 17# S-95 & N-80 LT&C Casing at 11,725'; Cemented w/ 750 Sx. Class "H", 3/4% CFR2 & 8# Salt/Sx.

Plug down 3:15 A.M. 9/6/73;

WOC 24 Hrs. & tested w/ 1500 psi for 30 Mins., held OK;  
Top Cement 9310'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. W. Wood TITLE District Production Mgr. DATE 9/12/73

APPROVED BY W. A. Gussert TITLE OIL AND GAS INSPECTOR DATE SEP 12 1973

CONDITIONS OF APPROVAL, IF ANY: