

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION.

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
2. Name of Operator Yates Petroleum Corporation		5. State Oil & Gas Lease No. K3402	
3. Address of Operator 207 South Fourth Street, Artesia, NM 88210		7. Unit Agreement Name	
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 No. Burton Flat Wolfcamp Gas THE West LINE, SECTION 20 TOWNSHIP 20S RANGE 28E NMPM.		8. Farm or Lease Name Stonewall DD Com.	
15. Elevation (Show whether DF, RT, GR, etc.) 3230' GR; 3265' KB		9. Well No. 1	
12. County Eddy			

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well is presently completed in Wolfcamp perforations 8917-8954' and production has declined to less than 1 BOPD. Propose to squeeze these perforations, drill out & clean hole to 11,260', perforate Morrow sands @ 11,250-254', 11,222-225' and 11,045-049', stimulate each interval as needed to return well to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddy M. Gressett TITLE Engineer DATE 8-10-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 11 1976

CONDITIONS OF APPROVAL, IF ANY: