

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-20892

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

K-3402

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER RECOMPLETION

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, New Mexico 88210

4. Well Location

Unit Letter N : 660 Feet From The South Line and 1980 Feet From The West Line

Section 20 Township 20S Range 28E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3250' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Plugback, perforate, Atoka, Strawn & treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

RU. Set tanks. Unset packer from 11022' POH. Set CIBP at 11000' w/35' cement on top.
3-30-91. Perforated Atoka 10834-10839' w/12 - .41" holes (2 SPF). Acidized perms 10834-839'
w/1000 gals 15% NEFE acid + 24 ball sealers. Swabbed with show of gas.
4-4-91. Moved packer and RBP. Set RBP 10800' and tested to 2000 psi. Perforated Atoka
10763-768' (2 SPF) and 10478-483' (2 SPF), total 24 - .41" holes. Acidized perms in two
stages w/2500 gals 15% NEFE acid. Swabbed dry. Made hourly runs - 1 BPH.
4-6-91. POH with packer and RBP. WIH and perforated Strawn 10316-320' and 10266-272' .
RBP set 10400' and packer set 10290'. Moved packer above all perms. Treated with 2500
gals 15% NEFE acid + 30 ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 4-10-91

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

APR 10 1991

CONDITIONS OF APPROVAL, IF ANY: