

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

IC 068399

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Active Drilling Well		7. UNIT AGREEMENT NAME Big Eddy	
2. NAME OF OPERATOR Perry R. Bass		8. FARM OR LEASE NAME Big Eddy Unit	
3. ADDRESS OF OPERATOR Box 1178, Monahans, Texas 79756		9. WELL NO. 37	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FN & WL of Section 10.		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10, T20S, R3E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3475' Gr.		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud date & surface casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded well at 9:00 AM, MDT, 7-26-73. Drilled 17 1/2" hole to 825' U.S. GEOLOGICAL SURVEY ARTESIA, NEW MEXICO

13 3/8" OD casing setting as follows:

No.	Jts.	Description	Thds. Off Length	From	
---		Rotary correction	21.90	0.00	21.9
20		13 3/8" OD, 48#/ft. H-40, ST&C csg.	761.56	21.90	783.4
---		Halliburton float collar:	1.60	783.46	785.0
1		13 3/8" OD 48#/ft. H-40 ST&C casing:	38.04	785.06	823.1
---		Halliburton float shoe	1.90	823.10	825.0

Bottom 3 joints sand blasted; welded and sealed with HOWCO Weld. Centralizer was run on each of bottom 3 joints. Circulated hole with 135 bbls. fluid. Rigged up Halliburton and cemented with 600 sks Class H cement containing 2% CaCl₂. Mixing time 23 minutes; slurry weight 14.0 PPG. Maximum pressure 500 psi. Plug down at 8:10 AM. Cement did not circulate. Ran 1" down outside of casing and tagged top of cement at 92'. Mixed and pumped 75 sks Class C cement containing 2% CaCl₂. Mixing time 8 minutes; slurry weight 14.0 PPG. Circulated cement. Job completed at 3:30 PM, 7-28-73. Drill 10' cement and float collar; tested casing to 600 psi for 30 minutes -- no loss. Drilled cement and float collar; tested casing to 600 psi for 30 minutes -- no loss.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Murty, Jr.

TITLE Division Production Clerk

DATE August 15, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

967-681