

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1421.

5. LEASE DESIGNATION AND SERIAL NO.

LC 068399

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

37

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T20S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER Active Drilling Well

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 1178, Monahans, Texas 79756

4. LOCATION OF WELL (Report location clearly and in accordance with any State rules.
See also space 17 below.)
At surface

1980' FN & WL of Sec. 10.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3475' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Ran drill pipe open-ended to 12,846' and circulated to condition hole.

Spotted plugs as follows:

- #1 50 sks C1 H, 4/10% HR-12 (14.8 PPG) @ 12,800'.
#2 50 sks C1 H, 4/10% HR-12 (15.2 PPG) @ 12,300'.
#3 50 sks C1 H, 4/10% HR-12 (15.3 PPG) @ 11,530'.
#4 50 sks C1 H, 4/10% HR-12 (15.2 PPG) @ 10,460'.
#5 50 sks C1 H (15.3 PPG) @ 8,700'.
#6 50 sks C1 H (15.3 PPG) @ 7,225'.
#7 50 sks C1 H (15.3 PPG) @ 5,700'.
#8 50 sks C1 H (15.8 PPG) @ 4,225'.

Plug #8 down @ 9:00 AM, 9-14-73.

Removed wellhead; spotted 10 sks cement at 20' extending to surface. Installed
regulation well marker on 9-19-73. Well plugged and abandoned.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. A. Murty Jr.

TITLE Division Production Clerk

DATE Nov. 12, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE