

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR "CATE"
(Other instruct. on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-911

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

El Paso "3" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 3, T-21-S, R-26-E

NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL ☐ WELL GAS ☐ WELL OTHER

Drilling

2. NAME OF OPERATOR

David Fasken ✓

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface2870' FEL & 2723.9' FNL - location is 489.1' FNL Lot
11 and 195.1' FEL Lot 11

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3188.6' GR.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cementing 13-3/8" casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

- Spudded 5:35 P.M., 8-3-73.
- Drilled 17-1/2" hole to 346 ft. - lost 100% mud returns at 217 ft.
- Cemented 13-3/8", H-40, 48#/ft. casing at 346 ft. with 200 sxs. Halliburton-Lite w/1/4# flocele/sx., 5# Gilsonite/sx. and 2% CaCl plus 100 sxs. Class "C" with 2% CaCl. - no mud or cement returns to surface during cementing. Fluid level came up to 10' of the cellar.
- Top of cement on back side of 13-3/8" casing was at 135' by temperature survey.
- Completed cementing operation with 4 cu. yds. of Ready-Mix concrete - filled-up annulus and bottom of cellar.
- Cut off 13-3/8" casing and welded on casing head.
- Installed B.O.P.
- Tested B.O.P.'s, casing and casing head to 1000 psig.
- Drilling ahead with 12-1/4" hole.

RECEIVED

AUG-7 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

TITLE

Agent

DATE

Aug. 6, 1973

(This space for Federal or State office use)

TITLE

DATE

APPROVED

AUG 13 1973

H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side