			1	10 1 0	
•		% . •.,		Capy as F	
Form 9-331 (May 1963)	DEPA	ป้าเfed states RTMENT OF THE INT	SUBMIT IN TRIPLICAT (Other instructions on verse side)		
	GEOLOGICAL SURVEY			_NM - 0400512	
		OTICES AND REPORT proposals to drill or to deepen or p PLICATION FOR PERMIT—" for s		6: IF INDIAN, ALLOTTEE OR TRIBE NAMI	
				7. UNIT AGREEMENT NAME	
WELL WEL		^{zr} Dry Hole		8. FARM OR LEASE NAME	
2. NAME OF OPERATOR			FEB 1 3 1974		
Coquina Oil Corporation -				Denegre-Federal	
200 Bldg. o	f Southwe]			
LOCATION OF WELL See also space 17 At surface	(Report locat	10. FIELD AND POOL, OR WILDCAT Wildcat			
1980' FEL & 660' FNL, Sec. 31, T20S, R27E			11. SEC., T., R., M., OR BLK. AND SURVEY OR ABEA -		
				Sec. 31, T2OS, R27E	
14. PERMIT NO.		15. ELEVATIONS (Show wheth	15. ELEVATIONS (Show whether DF, RT, GR, etc.)		
		G.L. 3214		Eddy N.M	
.6.	Check	Appropriate Box To Indica	ite Nature of Notice, Report, or	r Other Data	
NOTICE OF INTENTION TO:			SUBS	SUBSEQUENT REPORT OF:	
TEST WATER SHU	T-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT* X	
		CHANGE PLANS	(Other)		
REPAIR WELL				ults of multiple completion on Well	

- --- ---- (

Drilled 12" hole to 190' on August 6, 1973. Ran 8 5/8" 24# J-55 casing to 190' and mudded in. Drilled 8" hole to 415'. Ran 7" 23# J-55 casing to 415' and mudded in. Drilled 6 1/2" hole to 505'. Ran Gamma Ray-Neutron log to 504' on August 21, 1973. Pulled 8 5/8" and 7" casing. Ran 2 3/8" tubing to 500'. Spotted 50 sx. Class C cement. Spotted 100 sx. cement from 225'-125'. Put 20 sx. cement in top of 13 3/8" casing. Installed DHM on August 25, 1973.



7 19		
18. I hereby certify that the foregoing is true and correct SIGNED	TITLE Superintendent	DATE August 30, 1973
(This space for Federal of State office use)	TITLE	DATE
FEB 12 131	e Instructions on Reverse Side	