

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

AUG 16 '89

O. C. D.

WELL API NO. 30-015-20923
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. V-2394
7. Lease Name or Unit Agreement Name Allied Comm
8. Well No. 1
9. Pool Name or Wildcat Penlon Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☒ OTHER Reentry
2. Name of Operator Manzano Oil Corporation 505/623-1996
3. Address of Operator P.O. Box 2107/Roswell, NM 88202-2107
4. Well Location Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line Section 27 Township 20S Range 27E NMPM Eddy County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3259' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/9/89 Dig out cellar. Cut off dry hole marker. Install anchors & dig pit.
8/10/89 Pick up 7-7/8" bit & four 4-3/4" drill collars. TIH with 2-3/8" tubing. Tag cement @ 230'. Drill & fall out @ 375'. Ran rubing & tag green cement @ 2021'. Wash to 2229'. Drill to 2235'. Circulate clean & SI overnight.
8/11/89 Drill cement to 2235'. Fall out @ 2335'. Ran tubing to 278'. Tag green cement. Wash to 2887'. Drill soft cement to 2907'. Circulate clean.
8/12/89 Ran 88 jts 4-1/2" casing (2908.56'). Set @ 2908' KB. Circulate bottoms up. Cemented with 185 sacks 50/50 poz & 5#/SK salt. PD @ 10:55 a.m. 8/11/89. Test plug to 1000 psi. Held ok. Estimated top of cement @ 2250'.
8/15/89 Perforate 2792' to 2808' (16' 17 holes). Set packer @ 2708'. Acidized with 1500 gal 15% NEFE & 34 ball sealers. Total load to recover 60 bbl.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Adrian Williams TITLE Land/Drilling Secretary DATE August 15, 1989

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY

ADRIAN WILLIAMS

SANTA FE, DISTRICT II

APPROVED BY _____ TITLE _____ DATE AUG 17 1989

CONDITIONS OF APPROVAL, IF ANY: