

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions
verse side)

TE*
re

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0354232

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Elizando - Federal "A"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. La Huerta Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28-T21S-R27E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

1. OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

Cities Service Oil Company

3. ADDRESS OF OPERATOR

Box 4906 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FWL of Section 28, T-21-S,
R-27-E, Eddy County, New Mexico.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3211' GR.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3100' Lime & Shale. Prep to drill ahead. Drilled to a T.D. of 3100' and ran 14 Jts. (560.94') 10-3/4" OD 8R 45.5# K-55, 39 Jts. (1558.70') 10-3/4" OD 8R 40# K-55 and 25-1/2" Jts. (961.56') 10-3/4" OD 8R 32# H-40 Casing set and cemented @ 3100' w/1635 sacks Halliburton Lite w/5# Gilsonite and 1/4# Flocele/sack + 300 sacks Class "C" cement. Plug down @ 8:00 PM on 10-18-73. Circulated 75 sxs. Cement to pits. Bumped plug w/1500 psi - Held OK. WOC 20 hrs. Tested 10-3/4" casing to 1500 psi for 30 minutes with no drop in pressure. Drilled float and 1/2 of Shoe Jt. and tested with 1500 psi - Held OK. Drilled remainder of Shoe and 5' of formation to 3105'. Tested Shoe to 360 psi for 20 minutes - Held OK. USGS Office was notified and witnessed operations.

RECEIVED
OCT 25 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

19. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

DATE October 24, 1973

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

OCT 25 1973

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side