

UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIE
(Other instructions
verse side)TE*
-reForm approved
Budget Bureau No. 42-R1424.

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0354232	
2. NAME OF OPERATOR Cities Service Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 1919 Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement. See also space 17 below.) At surface 660' FNL, 1980' FWL of Sec. 28-T21S-R27E, Eddy County, New Mexico		8. FARM OR LEASE NAME Elizondo Federal A	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3211 GR		10. FIELD AND POOL, OR WILDCAT Burton Flat Morrow	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28-T21S-R27E	
		12. COUNTY OR PARISH Eddy	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 11,673' Sand. PBTD 11,015'. This well was plugged & abandoned in the following manner:

1. MIRU csg puller. Load tbq with water, unseat pkr & pulled tbq & pkr.
2. Set CIBP @ 11,050' & dumped 35' of cement on top of CIBP to plug off Morrow perfs. 11,262' - 11,597'. TOC 11,015'.
3. Shot 5-1/2" csg off @ 7820' & pulled 194 Jts. (7868') 5-1/2" OD 17# N80 casing.
4. Circulated hole with mud laden fluid.
5. Spotted 60 sack cement plug 1/2 in & 1/2 out 5-1/2 casing stub.
6. Spotted 75 sack cement plug 7185' - 7035' across top of 2nd Bone Springs.
7. Spotted 75 sack cement plug 6500' - 6350' across top of 1st Bone Springs.
8. Spotted 75 sack cement plug 5175' - 5025' across top of Bone Springs.
9. Spotted 50 sack cement plug 3150' - 3050' 1/2 in & 1/2 out of 10-3/4" casing shoe.
10. Spotted 50 sack cement plug from 50' to 0' with a 4" dry hole marker extending 4' above the surface to designate a plugged & abandoned location.
11. Cleared location of all casing & debris.

Don Gordon of USGS witnessed Job.

RECEIVED

JUL 14 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Oper. Mgr.

DATE July 12, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: