

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)DATE
on re-Form approved by *C. G.*
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

IC 067964

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

38

10. FIELD AND POOL, OR WILDCAT

Quahada Ridge Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 34, T21S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 2760, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FWL of section Unit letter C.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3426.5' GL 3444' KDB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Workover

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*3-3-76: Rigged up service unit. Pumped 80 bbls KCl water down tubing - casing full.
Pulled 2 7/8" tubing and Baker packer.3-4-76: Ran tubing with cement retainer - set @ 13,040'. Pumped 100 sks Class H
cement (squeezed perforations 13,068'-13,212'). Reversed out 35 sks. Picked up tubing
to 12,950' and spotted 250 gals acetic acid from 12,950' to 12,700'. Flushed with KCl
water - pulled tubing.3-5-76: Dresser Atlas perforated Morrow section w/1JSPF from 12,754-60', 12,865-68',
12,870-72', 12,875-82' and 12,895-99'. Tagged bottom at 13,045'.3-6-76: Ran tubing and Baker Model R packer - set @ 12,620'. Rigged to swab. Top
fluid 200' from surface. Swabbed to 7000' - gas burning ahead of swab.3-7-76: Shut down.3-8-76: 37 hour SITP 2500#.3-9-76: CITP 2700#. Acidized with 4500 gals 7 1/2% MF acid with N₂ and ball sealers.3-10-76: Opened well to pit - bled back N₂. Removed tree - installed BOPs - un-
seated packer - reversed out KCL water, acid and N₂. Pulled tubing and packer.3-11-76: Swabbed tubing dry. Acidized with 2500 gals 7 1/2% MS & 37 ball sealers.
ISIP 5200#. Flowed to pit then put on line @ 5:15 PM a/r 1027 MCFD.3-12-76: Flowing a/r 1087 MCFD, 1050# TP, 20/64" choke.3-13-76: Flowing a/r 1449 MCFD, 1.15 BOPD, 3.5 BOPD, 950# TP, 20/64" choke.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Montoya, Jr.

TITLE

Division Production Clerk

DATE

April 27, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
APR 28 1976
H. L. BEEKHUIS
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.