

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other Instructi
verse side)CATE*
OR re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-6008-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

Cities Service Oil Company

DEC - 6 1973

3. ADDRESS OF OPERATOR

Box 4906 - Midland, Texas 79701

O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

ARTESIA, OFFICE

1980' FSL & 1980' FEL of Sec. 17 - T21S - R22E,
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4462.56' GR

8. FARM OR LEASE NAME

Loafer Draw Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat - Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17-T21S-R22E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

T.D. 1682' Lime. Prep. to drill ahead. Spudded 11/22/73. Set 22' of 13-3/8" Conductor Casing. Drilled to a TD of 1682' and ran 40-1/2 Jts. of 9-5/8" OD 40#, N-80 & K-55, LT & C and ST & C Casing at 1682' with 335 sx Halliburton Lite w/5# Gilsonite 1/4# Flocele & 2% Ca Cl/sx, followed by 300 sx Class C w/2% Ca Cl. Plug down at 6:30 AM, 11/27/73. Cmt. did not circulate. (Leon Beekman, USGS, witnessed job) WOC 5-1/2 hrs. TC 860'. Ran 1" tbq. in annulus to 635' & re-cemented as follows:

No. Sx & Type Cement

Fill Up

Stage #	50 Sx Class C w/4% Ca Cl
#1	" " " " "
#2	" " " " "
#3	" " " " "
#4	" " " " "
#5	" " " " "
#6	" " " " "

No Fill
No Fill
243' Fill
166' Fill
116' Fill
Cmt. C

RECEIVED
DEC - 3 1973
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Cement fell back 15'. Filled with pea gravel. Job Complete 5:30 AM, 11/28/73. Starte pressure testing well at 10:00 PM, 11/28/73. Tested casing & BOP to 1500 psig for 30 minutes. Held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

DATE 11/30/73

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED

DEC - 8 1973

U.S. GEOLOGICAL SURVEY
RESTON, VIRGINIA