

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0560293

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 4

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T-20-S, R-28-E.

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER DRY HOLE

2. NAME OF OPERATOR

Jake L. Hamon ✓

3. ADDRESS OF OPERATOR

908 Vaughn Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1830' FSL & 1980' FEL of Section 4, T-20-S, R-28-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3300' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Well spudded 1:00 P.M. 11-21-73. 12" hole drilled to 216' and 9-5/8" 40# J55 casing set at 216' GR and cemented to the surface with 225 sacks at 5:00 P.M. 12-4-73. 8-1/2" hole was drilled to 510' and 7" casing set but not cemented. 6-1/2" hole was drilled to 1000'. TD reached at 4:00 P.M. 1-9-74.

T/Rustler	265' (+3035')
T/Salt	513' (+2787')
B/Salt	713' (+2587')
T/Tansill	814' (+2486')
T/Yates	925' (+2375'), no show, no porosity.

Propose to plug and abandon as follows:

25 sacks	975-867' (108')
40 sacks	513-412' (101')
50 sacks	275-153' (122')
10 sacks	Top surface casing (23') with marker.

Verbal permission to plug and abandon as above given by Mr. Jim Knauf 1-9-74.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Superintendent

DATE 1-10-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

MAR 13 1974

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED

JAN 11 1974

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO