

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 1D
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Citizens Service Oil Co.</u>		Lease <u>Tracy A Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>660 N 2310 W</u>	Section <u>33</u>	Township <u>21</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment <u>Rotary to start approx. 1-1-74</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>20"</u>	<u>16"</u>	<u>65"</u>		<u>400</u>	<u>350 cgs.</u>
<u>14 3/4"</u>	<u>10 3/4 11 3/4"</u>	<u>40.5-45.5+51</u>		<u>3200</u> 3550	<u>2100 "</u>
<u>9 1/2</u>	<u>5 1/2</u>	<u>17+20</u>		<u>11800</u>	<u>1000</u>

Casing Data:

Shut.
Surface 118 joints of 11 3/4 inch 60 # Grade C-45 V STC
Used (Approved) (~~Rejected~~)

Inspected by S. A. Gorman date 2-7-74

Cementing Program

14 3/4" 3244
Size of hole 15" 6.675 Size of Casing 11 3/4 Sacks cement required 193.5

Type of Shoe used Guid Float collar used Yes Btm 3 jts welded Yes

TD of hole 3244 KB Set 3244 3/4 Feet of 11 3/4 inch 60 # Grade C-45-V

New-used csg. @ 3244 3/4 with 300 sacks neat cement around shoe 14.6 #
+ 16.35 sax Flowline Data additives 5 G. Gelsite 1/4" Flocc 100.0

Plug down @ 9:17 (AM) (PM) Date 2-8-74

Cement circulated Yes No. of Sacks 300/58

Cemented by H. H. H. H. Witnessed by S. A. Gorman

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 1st 4' fine jts rough past, 3 Baskets Between 600'-700' 4 Bts, 13.57

Surface TD 394 KB From 14 3/4 16" 75" J-55 6 1/2" H-40

Cut w/ 450/8X 14 3/4" Flocc 2% SC PD 6:20 AM 1-29-10

Cure 51st