

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 17101

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Government-W

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22-T20-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Cities Service Oil Company ✓

MAR 28 1974

3. ADDRESS OF OPERATOR

Box 4906 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FWL of Sec.22-T20S-R28E, Eddy Co., New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3236' GR.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data:

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3005' Lime. Prep to drill ahead. Drilled to a T.D. of 3000' and ran 59 Jts. (2039.54') 9-5/8" OD 36# K-55 and 31-1/2 Jts. (942.46') 9-5/8" OD 32# H-40 casing set and cemented @ 3000' w/850 sacks Halliburton Lite w/1/4# Flocele/sack + 300 sacks Class H w/2% CaCl cement. Bumped float w/1300# - Held O.K. Plug down @ 5:20 P.M. on 3-19-74. Circulated 200 sacks cement to pits. WOC 34 Hrs. Drilled float and 1/2 shoe. Tested 9-5/8" OD casing to 1500# for 30 minutes with no drop in pressure. Drilled rest of shoe and 5' of formation. Pressure tested w/Halliburton to 380# for 15 minutes - Held O.K. (eq. to 10.5#/gal. mud)

U.S.G.S. was notified and witnessed job.

RECEIVED

RECEIVED

MAR 28 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

MAR 28 1974

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

E. Spiller

TITLE

Region Oper. Mgr.

DATE

March 22, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APPROVED
MAR 28 1974
E. Spiller