Dec. 1973	HANTER ATTER	Budge	et Bureau No. 42-R1424
	UNITED STATES TO UTIL COME. COM	STLEASE	
	DEPARTMENT OF THE INTERIOR ( 20)	NM01165	
	GEOLOGICAL SURVEYArtesia, Md 808	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS		7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plus back to a different reservoir. Use Form 9–331–C for such proposals.)		8. FARM OR LEASE NAME	
1. oil ,	gas 🔯 other	Yates Federal	
well 4	- Well	9. WELL NO.	
_	OF OPERATOR AUG 16'89	10. FIELD OR WILDCAT N	A115
	ESS OF OPERATOR C. C. D.	Burton Flat E.	AME
	W. Wall, Ste. 900	11. SEC., T., R., M., OR B	LK. AND SURVEY OR
	TION OF WELL (REPORT LOCATION CLEARLY. See space 17	~  .==.	
- below.		Sec. 18, T-20-S,	
	URFACE:	12. COUNTY OR PARISH	13. STATE
	OP PROD. INTERVAL: 660' FEL & 1980' FNL OTAL DEPTH:	Eddy	NM NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		14. API NO.	
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW	DE KDS VND MD)
		3265' GL	DF, RDB, AND WD)
TEST WAT FRACTURE SHOOT OF REPAIR W PULL OR	R ACIDIZE	(NOTE: Report results of mi change on Form 9–	
includ	RIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating estimated date of starting any proposed work. If well is ured and true vertical depths for all markers and zones pertine	directionally drilled, give sub ent to this work.)*	surface locations and
6-20-89	1- 0/011 1 6 1		
6-21-89 RU & ran GR log f/10,600-10,400'. Set CIBP @ 11,220'. Dumped 35' cmt to top CIBP. (New FBID 11,185'). Perf Strawn 10,446-54', 10,483-90', 10,504'-08', 10,573-76'. TIH w/pkr & tbg. Test in hole to 5000#. Set pkr @ 10,361'. ND BOP. NU WH. Test annulus to 500#-OK.			
6-22-89	5-22-89 Swb well dn. RU Western Co. & acidize Strawn w/2300 gal 15% NeFe w/additives using 52 ball sealers. Max press 5000#, Min press 3600#, ATP 4000#, AIR 2 bpm. Had ball out during treatment. ISIP 3500#, 15 min to vacuum. Flwd well overnight on 3/8" ck. Prep to install test separator		
6-23-89	Install production facilities. Prep to turn well	to sales line.	Post ID-
thru 6-28-89	install production facilities. Trep to turn were		Post ID- 8-15-89 PXA MO
6-29-89	Well SI, WO 4-pt. test.		PXA mo
thru 7-6-89	, .		
7-7 <b>-</b> 89	Rn 4-pt test. CAOF 1.552 MCFD. (test attached).	_	
Subsurfac	ce Safety Valve: Manu. and Type	Set	Ft.
18. I here	eby certify that the faregoing is true and correct		
	Ontie and Usey THE Drig. Secretary (This space for Federal or State of	CY DATE 7/13/89	
	(This space for Federal or State of	office use)	
	TITLE		
APPROVED CONDITION	NS OF APPROVAL, IF ANY:	DATE	

\*See Instructions on Reverse Side

696 1 April 1

AND 197-11 1034 WILLSON