N. M. O. C. C. COPY
ES
SUBMIT IN TRIPL
(Other instructions on UN. _D STATES

Caszy &SF Form approved.

Budget Bureau No. 12 R1424.

DESIGNATION AND SERIAL NO.

DEPART	MENT OF THE INTERIOR	OR verse side)	LC-063567
SUNDRY NO	TICES AND REPORTS Cosals to drill or to deepen or plug be CATION FOR PERMIT—" for such pre	N WELLS lek to a different reservoir. possils ::	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL XX GAS OTHER NAME OF OPERATOR			Yates Federal 8. PARM OR LEASE NAME
Harvey E. Yates Cor	npany	O.C.C.	9. WELL NO.
Suite 1000-Security LOCATION OF WELL (Report location See also space 17 below.) At surface	Nat'l Bank Bldg Received and in accordance with any state of Section 7, T-20S,	218f6 teduitements.	17 10. FIELD AND POOL, OR WILDCAT McMillan, S.R. Queen 11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
14. PERMIT NO.	15. ELEVATIONS (Show whether DF.	RT, GR, etc.)	Sec. 7, T-20S, R-27E 12. COUNTY OR PARISH 13. STATE Eddy NM
16. Check	Appropriate Box To Indicate N	ature of Notice, Report, or (Other Data
	NOTICE OF INTENTION TO:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL, (Other) 17. DESCRIBE PROPOSED OR COMPLETED	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS OPERATIONS (Clearly state all pertinon	1 Completion or Recom	e of multiple completion on Well pletion Report and Log form.)
proposed work. If well is dire nent to this work.) *	ectionally drilled, give subsurtace loca	tions and measured and true serve	cal depths for all markers and zones perti-
4/14/74	Ran 382.10' of 8 5/8" plug down.	casing, cemented wi	th 50 sx.,
4/29/74	Ran 950' of 7" casing	g, 175 sx. cement.	
5/22/74	Perfs 850-860, 2 JSPF	•	•
5/22/74	Acidized with 500 gal	llons of XF63 acid.	
5/24/74	8 hr. bail test: 90-	-100 bw.	
		1	RECEIVED JAN 2 1975 JAN 2 1975 U.S. GEOLOGICAL SURVEY MEXICO
18. I hereby certify that the forego	ng is true and correct		10/21/74

SIGNED Debra Thalore	TITLE _	Production Clerk	DATE _12/31/74
(This space for Federal of State office use) ALPROVED BY ALPROVED BY ALPROVAL, IF ANY:	TITLE _		DATE

*See Instructions on Reverse Side