

NO. OF COPIES RECEIVED	✓
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

MAR 22 1974

O. C. C.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cities Service Oil Company ✓	8. Farm or Lease Name Simpson A Com.
3. Address of Operator Box 4906 - Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>810</u> FEET FROM THE <u>East</u> LINE, SECTION <u>29</u> TOWNSHIP <u>21S</u> RANGE <u>27E</u> NMPM.	10. Field and Pool, or Wildcat Undes. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3154' GR.	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 420' Lime. Prep to drill ahead. Spudded on 3-16-74 and drilled to a T.D. of 420'. Ran 8-1/2 Jts. (400.20') 13-3/8" OD 48# H-40 casing set and cemented @ 420' w/425 sacks Class C w/1/4# Flocele/sack + 2% CaCl cement. Circulated 30 sacks to pits. Plug down @ 1:25 P.M. on 3-17-74. Bumped float with 1000# Held O.K. WOC 24 hrs. Tested 13-3/8" OD casing to 1000# for 30 minutes with no drop in pressure.

U.S.G.S. notified but did not witness.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. Spindler TITLE Region Oper. Mgr. DATE March 21, 1974

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE MAR 22 1974

CONDITIONS OF APPROVAL, IF ANY: