

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Cities Service Oil Co.</u>		Lease <u>Simpson "A" Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>H</u>	Section <u>29</u>	Township <u>21</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment <u>Rotary</u> <u>3-15-74</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>20"</u>	<u>16" 13 7/8"</u>	<u>65# 48</u>		<u>400'</u>	<u>350 circ</u>
<u>14 3/4"</u>	<u>10 3/4" 9 5/8"</u>	<u>32.7-40.5-45.5</u>		<u>3800</u>	<u>1900 "</u>
<u>9 1/2"</u>	<u>5 1/2"</u>	<u>17, 20</u>		<u>11,800</u>	
Casing Data:					
Surface <u>87</u> joints of <u>9 5/8</u> inch <u>32, 36, 40 #</u> Grade <u>H-40 K-55</u>					
(Approved) (Rejected)					
Inspected by <u>J. A. Williams</u> date _____					
Cementing Program					
Size of hole <u>12 1/4"</u> Size of Casing <u>9 5/8</u> Sacks cement required <u>1130</u>					
Type of Shoe used <u>Guide</u> Float collar used <u>Fusent</u> Btm <u>2</u> jts welded <u>Yes</u>					
TD of hole <u>3160.70K</u> Set <u>3051.20</u> Feet of <u>9 5/8</u> Inch <u>est</u> # Grade <u>H-40 - K-55</u>					
New-used csg. @ <u>3051.20</u> with <u>300</u> sacks neat cement around shoe <u>2800 cc 14.8</u>					
+ <u>830</u> sack <u>Alumina</u> with additives <u>5# Glycerine 4# Flocc 2% cc 13.0</u>					
Plug down @ <u>1:20</u> (AM) (PM) Date <u>3-28-74</u>					
Cement circulated <u>No</u> No. of Sacks <u>None</u>					
Cemented by <u>Halliburton</u> Witnessed by <u>J. A. Williams</u>					
Temp. Survey ran @ <u>7:55</u> (AM) (PM) Date <u>3-28-74</u> top cement @ <u>720'</u>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Taped 679' 9:06 AM Cut w/ 50/sy (Class C 4% cc 14.8</u>					
<u>PD 9:30 AM Taped at 11:38 AM 1446' Cut w/ 150/sy Class</u>					
<u>C 2% cc 14.8 Circ. 2 1/2/sy</u>					