

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLET
(Other Instructions
on reverse side)

16

Form approved
Budget Bureau No. 42-100-1

5. LEASE DESIGNATION AND SERIAL NO.

NM 2377

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL ☐ GAS ☐ WELL ☒ OTHER ☐

2. NAME OF OPERATOR
Cities Service Oil Company

3. ADDRESS OF OPERATOR
Box 1919 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FSL & 660' FEL of Sec. 11-T20S-R28E, Eddy Co., New Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3562' GR.

MAY 21 1974

O. C. C.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Government Y

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT

Undes. Russell Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11-T20S-R28E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3005' Lime. Prep to drill ahead. Drilled to a T.D. of 3000' and ran 23 Jts.(932.55') 9 5/8" OD 40# K-55, 35 Jts.(1196.34') 9 5/8" OD 36# K-55 and 19 1/2 Jts.(853.11') 9 5/8" OD 32# H-40 casing set and cemented @ 3000' w/900 Sacks Halliburton Light w/1/4# Flocele and 5# Gilsontite/sack + 300 sacks Class "C" cement. Plug down @ 6:25 AM on 5-14-74. Bumped float w/1400# - Held O.K. Circulated 190 sacks cement to pits. WOC 26 Hrs. Drilled float and 1/2 of shoe joint. Pressured to 1500# - Held O.K. Drilled rest of shoe joint and 5' of new hole to 3005'. Tested shoe and formation to 350# with Halliburton at rate of 1/2 B/M for 15 minutes - Held O.K.

USGS was notified but did not witness job.

RECEIVED

MAY 20 1974

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

E. Schilder

TITLE Region Operation Manager

DATE May 17, 1974

(This space for Federal or State office use)

APPROVED BY

CONCURRENCE OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

