

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructi
verse side)DATE
in reForm approved.
Budget Bureau No. 42-11424.

5. LEASE DESIGNATION AND SERIAL NO.

0915

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

40

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T21S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE
New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Active Drilling Well

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 1178, Monahans, Texas 79756

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 1980' FEL of section - unit letter G.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3440' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud date & 16" casing setting

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths, and markers and zones pertinent to this work.) *

Spudded 20" hole @ 9:00 AM. CDT. 3-22-74.

Ran 16" casing as follows:

No. Jts.	Description	Length	From	To
--	Rotary correction	21.85	0.00	21.85
8	16" OD, H-40, 65#/ft. ST&C casing	334.98	21.85	356.83
--	Halliburton float collar	1.60	356.83	358.43
1	16" OD, H-40, 65#/ft. casing	47.00	358.43	405.43
--	Halliburton float shoe	1.80	405.43	407.23

Cemented as follows:

Circulated and mixed mud for one hour; mixed 475 sacks class "C" cement containing 2% CaCl and 1/4# of Flocele per sack. Slurry weight 14.8 PPG; mixing time 25 minutes. Pumping time 15 minutes. Maximum pressure 400 psi.

Circulated out 25 sacks. Pumped plug with 600 psi. Plug down at 2:55 a.m. CDT.

3-24-74:

24-hour recap: 20 1/2 hours, WOC -- nipping up -- and testing Hydril to 600 psi. 1 1/4 hours, drilling float collar, cement, float shoe and 2' of formation. 1/2 hour, testing 16" casing to 600 psi. 1 3/4 hours, drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Div. Prod. Clerk

DATE Apr. 1, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.