

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on re-  
verse side)Form approved. 10/1/74  
Budget Bureau No. 42-R1424

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		RECEIVED	
2. NAME OF OPERATOR MONSANTO COMPANY		APR 24 1974	
3. ADDRESS OF OPERATOR 101 North Marienfeld, Midland, Texas 79701		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990/8N 2310/E 330' FSL & 330' FWL Section 13		10. FIELD AND POOL, OR WILDCAT Burton Flat - Morrow	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) Gr. Elev. 3294; Est KB Elev 3309'	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T-21S, R-26E		12. COUNTY OR PARISH Eddy	
13. STATE New Mexico			

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded 17½" hole 6:00 PM 3/26/74;

Drilled 17½" hole to 600' &amp; set 13 3/8" 54.5# K-55 ST&amp;C Casing at 600'; Cemented w/ 600 Sx. Lite Wt w/ 5% Silica ½# Gel flake, 2% CaCl + 150 Sx. Class "C" w/ 2% CaCl &amp; ½# Gel; Plug down 9:00 PM 3/29/74; did not circulate; Ran 1" &amp; tagged cmt at 518' &amp; cemented w/ 300 Sx. Class "C" w/ 2% CaCl in 5 stages, no fill; Cemented thru 1" w/ 100 Sx. 50/50 lite wt Pozmix w/ 2% Gel &amp; ½# Gel flakes w/ 2% CaCl;

Top cement 568';

Cemented w/ 50 Sx. RFC cement; cemented in 7 stages w/ 450 Sx. 50/50 lite pozmix w/ 2% CaCl; Cement circulated. Job complete 9:30 AM 4/1/74.

WOC 18 Hrs. &amp; tested w/ 1000 psi for 30 Mins., held OK.

RECEIVED

APR 18 1974

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

## 18. I hereby certify that the foregoing is true and correct

SIGNED

W. W. Wood

TITLE District Production Mgr.

DATE 4/17/74

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

APR 23 1974

K. L. BECKMAN  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side