

DISTRIBUTION		
SANTA FE	/	
FILE	/	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	/	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
~~NY-16624~~ K-4193

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
TENNECO OIL COMPANY ✓

3. Address of Operator
6800 Park Ten Blvd., Suite 200 N. *San Antonio, TX 78213*

4. Location of Well
UNIT LETTER F 1650' FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 21S RANGE 26E NWPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3284' KB

7. Unit Agreement Name

8. Farm or Lease Name
Ocotillo Hills *Com*

9. Well No.
1

10. Field and Pool, or Wildcat
Avalon Wolfcamp

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Fracture Treat & Shoot or Acidize</u> <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Blanking plug to plug off Morrow by setting in Otis "N" Nipple. We plan to perforate additional Wolfcamp 8907, 09, 11, 14, 17, 21, 23, 26, 29, 33, 37, 40, 44, 77, 78, 79 w/1JSPF. These new perms plus old Wolfcamp perms 8948-68 will be acidized with 2000 gals. Mod 202 & 54 ball sealers, and then fracture treated with 80,000 gals. Versagel 1500 and 185,500 #20-40 sand. The well will be cleaned up and then put back on production down sales line.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Mary Hall* TITLE PRODUCTION ANALYST DATE 1/30/81

APPROVED BY *Mr. Williams* TITLE OIL AND GAS INSPECTOR DATE FEB 06 1981

CONDITIONS OF APPROVAL, IF ANY: