

PROPOSED PLUGGING DIAGRAM
 PENN FED. #1
 1980' FNL & FWL SEC. 31
 T-20S, R-30E
 EDDY COUNTY, N.M.

TOPS

FT SACKS

SALT 1200'

PLUG #9 0-50'

20

PLUG #8 200-500'

110

13 3/4" @ 451'
 CMT TO SUIT.

BASE OF,
 SALT 1600'

D.V. TOOL @ 1630'

PLUG #7 1550-1650'

40

2 3/8" @ 4066'
 CMT TO SUIT

PLUG #6 4016-4116' - TAG

40

DELAWARE
 Ø 4400'

PLUG #5 4350-4500'

50

Base Shrink
 6436'

PLUG #4 6400-6550'

50

Base Shrink Porosity
 7400'

PLUG #3 7350-7500'

50

2 1/2" STUB ± 2000'
 TOP CEMENT 8260'

PLUG #2 7250-8000' - TAG
 CUT 2 1/2" CASING @ ± 2000'

50

WOLF CREEK
 9846'

PLUG #1 8200-11746'

125

STRAWN
 11067

ATOKA
 11211

MOKKOW
 11775

PERFORATIONS
 11738-746

2 1/8" STUB @ 12066'
 TO 12570'

