

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIP DATE*
(Other instruction, 1 re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15002

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER2. NAME OF OPERATOR
Meadco Properties, Ltd.

AUG 19 1974

8. FARM OR LEASE NAME
Lario-Federal3. ADDRESS OF OPERATOR
P. O. Box 2236, Midland, Texas 79701O. C. C.
ARTESIA, OFFICE9. WELL NO.
14. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface10. FIELD AND POOL, OR WILDCAT
McMillan (Morrow)

1650' FNL & 2160' FEL, Sec. 17, T-20-S, R-27-E

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-20S-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3633 Gr.

12. COUNTY OR PARISH
Eddy13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) running 8-5/8" casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 2707'. Ran 63 jts. 8-5/8" 24# ST&C casing. Set at 2707'. Cemented with 1200 sx Halliburton Lite with 5# gilsonite & 1/4# Flocele per sack. Followed by 200 sx Class C with 2% calcium chloride. Plug down 8:45 p.m. 8/11/74. Cement did not circulate and 50 sx Class C cement with 2% calcium Chloride was used outside 8-5/8" casing. Cement circulated but dropped back. Used additional 30 sx plain cement to bring cement to surface. WOC 24 hrs. Tested to 1000# for 30 min. Tested okay.

Drilling at 2770' lime and sand on August 13, 1974.

RECEIVED
AUG 14 1974
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 8/13/74

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side