

Test #6 Repeated test. Pressured to 2500# (as directed) with same leaks. Tightened.

Test #7 Repeated test. Pressured to 2500# with leak to door seal of blind rams bop (pit side). Tightened.

Test #8 Repeated test. Pressured to 2500# with loss of approximately 100# during first fourteen minutes then leveling out for remaining one minute of test.

NO VISIBLE LEAK. PRESSURE LEVELING OUT TOWARDS APPROXIMATELY 2400#.

---

TESTING: Pipe Rams with outside valve closed off stack on chokeline - pressure applied down drill pipe.

Test #9 Pressured to 200# and released air; repressured to 2500# with loss of approximately 50# during first eight minutes then leveling out for remaining one minute of test.

NO VISIBLE LEAK. PRESSURE STEADY AT APPROXIMATELY 2500#.

---

START CHART #2

TESTING: Inside valve next to stack on chokeline with pipe rams closed - pressure applied down drill pipe.

Test #10 Pressured to 2500# with loss of approximately 100# during first eleven minutes then leveling out for remaining two minutes of test.

NO VISIBLE LEAK. PRESSURE LEVELING OUT TOWARDS APPROXIMATELY 2400#.

---

TESTING: Hydril with inside valve closed next to stack on chokeline.