

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

16994

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. DIRM OR LEASE NAME

Allen F Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 4, 22-S, 25-E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

1. OIL ☐ WELL GAS ☐ WELL OTHER ☒

Dry hole

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FN & EL, Section 4, 22-S, 25-E

O. C. C.
ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Plug and Abandon

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

2215' TD.

Reached TD of 12-1/4" hole at 2215' at 8:15 AM, September 2, 1974. Ran logs. No indication of commercial production. Obtained verbal permission from Mr. James A. Knauf to plug and abandon as follows: Set 200 sack Class Cement plug No. 1 from 1900' to 2215'. Load hole with gravel to 857'. Load hole with 125 barrels of 8.5# 36 viscosity mud to surface. Spot 65 sack Class C cement plug No. 2 from 757' to 857'. Spot 65 sack cement No. 3 from 307' to 205', across 13-3/8" shoe at 257'. Spot 20' cement plug No. 4 from 20' to surface. Install dry hole marker and clean location.

RECEIVED

SEP 16 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Engineer

DATE September 9, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NOV 6 - 1974

H. L. BEEKING
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side