

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

16994

6. IF INDIAN, ALIOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Allen F Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 4, 22-S, 25-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1650' FN &amp; EL, Section 4, 22-S, 25-S

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Plugged and abandoned

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per-  
tinent to this work.)\*

TD 2215'.

Reached TD of 12-1/4" hole at 2215' at 8:15 AM, September 2, 1974. Ran logs. No indications of commercial production. Spotted 200 sack Class C cement plug No. 1 from 1900' to 2215'. Loaded hole with gravel to 857'. Loaded hole to surface with 125 barrels of 8.5# 36 viscosity med. Spotted 65 sack Class C cement plug No. 2 from 757' to 857'. Spotted 65 sack Class C cement plug No. 3 from 307' to 205', across 13-3/8" shoe at 257'. Spotted 20' cement plug from 20' to surface. Installed dry hole marker. Plugged and abandoned September 5, 1974. Will advise when location is ready for your final inspection.

RECEIVED

DEC 24 1974

D. C. E.  
ARTESIA, OFFICE

I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Engineer

DATE

September 6, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side