

NM OIL CONS. COMMISSION

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210  
RECEIVED NM-17098

RECEIVED

MAY 05 1983

O. C. D.  
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Depleted Oil Well  
well well

2. NAME OF OPERATOR  
Penroc Oil Corporation ✓

3. ADDRESS OF OPERATOR  
P. O. Drawer 831, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' fNL, 990' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☒  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-18-83 T.D. 10,393' P.B.T.D. 9600'

1. Set CIBP @ 9075' by Wireline. Bailer dump 35' cement on top. Plug will be above Wolfcamp perfs @ 9142-9149'.

2. Cut off 4 1/2", 11.60#, N-80, casing at approximately 8300' and pull. Top of cement behind casing @ 8500' by temp. Svy.

3. Set 150' cement plug 8375-8225' (75' in and out of 4 1/2" csg. stub.).

4. Set 100' cement plug 4580-4480' (Across top of Bone Spring).

5. Set 100' cement plug 2710-2610' (50' in and out of 8 5/8" csg. bottomed @ 2660'). ← tag plug

6. 100' cmt. plug 375'-275'.

7. 0. Set 15 sack cement plug in top of 8 5/8" csg. w/dry hole marker set in place.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. J. Dickey TITLE President

DATE 4-18-83

APPROVED

(This space for Federal or State office use)

APPROVED BY W. CHESTER TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

MAY 4 1983