

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Depleted Oil Well

2. NAME OF OPERATOR
PENROC OIL CORPORATION

3. ADDRESS OF OPERATOR
P. O. Drawer 831, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' fNL, 990' fWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☒
☐
☐
☒

NM C CONS. COMMISSION
Drawer DD
Form Approved.
Budget Bureau No. 42-R1424

Antesita, NM
NM-17098

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED BY

8. FARM OR LEASE NAME JAN 16 1984
MLT Federal

9. WELL NO. O. C. D.
1 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME
Winchester-Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
1-20S-28E

12. COUNTY OR PARISH Eddy
13. STATE New Mexico

14. API NO.
30-015-21338

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3271' GR, 3291' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 6-16-83 Set 4½" CIBP @ 9075'. Bailer dump 35' cement on top of plug.
6-17-83 Cut off 4½", 11.60#, N-80 csg. @ 8300'. Recovered 8300'.
6-20-83 Set 150' cement plug 8375'-8225' (75' in and out of 4½" casing stub)
Tagged @ 8225'.
Set 100' cement plug @ 4580'-4480'.
6-21-83 Set 100' cement plug 2710'-2610' (50' in and out of 8 5/8" csg.).
Tagged plug @ 2610'.
Set 100' cement plug 375'-275'.
Set 15 sxs. cement plug in top of 8 5/8" csg. w/dry hole marker.
Surface location to be cleaned, leveled, ripped, etc, according to
BLM Stipulations.

When completed will submit notice for final approval.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED P. V. Chester TITLE President DATE 7-7-83

APPROVED _____ (This space for Federal or State office use)

APPROVED BY (Only Sgd.) PETER V. CHESTER DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FEB 14 1984

See Instructions on Reverse Side