

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other Instruc
verse side)LICATE
on reForm approved
Bureau Order No. 42-R1124

5. LEASE DESIGNATION AND SERIAL NO.

NM-029128

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Catclaw Draw Unit

8. FARM OR LEASE NAME

Catclaw Draw Unit

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Catclaw Draw Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

27-21S-25E

1.

OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Hanagan Petroleum Corporation

OCT 8 1974

3. ADDRESS OF OPERATOR

P. O. Box 1737, Roswell, New Mexico 88201 O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1650' FSL & 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, FT, GR, etc.)

3459' GR

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

9/11/74: Spud 10:30 AM, Moranco Contractor.

9/13/74: TD 185', 20" hole, ran 6 jts. 16" 65# casing set @ 185' w/200 sx. Class "C" +
2% CaCl. Plug down 3:00 AM. Cement circ. 1.32 slurry vol. cu. ft./sx. 750°
temp. Slurry mixed, est. fm. temp. @ 750°, compressive strength 565#. Drld
plug 3:30 PM 9/13/74. WOC 12 hrs. Press. up 600# for 30", no press. drop.9/17/74: TD 2195', 14-3/4" & 12-1/4" hole, ran 53 jts. 9-5/8" 40# & 36# LT&C (2222'),
set @ 2195', cemented w/800 sx. Howco light, 1/4# flocl, 5# gilsonite, 2% CaCl +
150 sx. Class "C" 1/4# flocl, 2% CaCl. Plug down 2:15 PM 9/17/74. Cement circ.
WOC 31½ hrs 9/18/74, drld. plug 9:45 PM 9/18/74. Press. up 1500#, 30", OK, no
press. drop. Yellow Jacket B.O.P. & manifold w/5000#, OK. Hydrill w/3000#, OK.RECEIVED
SEP 28 1974
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Southland

TITLE

Agent

DATE

9/25/74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DISTRICT ENGINEER

DATE

OCT 4 1974