

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ RECEIVED

2. NAME OF OPERATOR

Corinne Grace

3. ADDRESS OF OPERATOR

P. O. Box 1418, Carlsbad, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)  
See also space 17 below.)  
At surfaceO. G. C.  
ARTESIA, OFFICE

2016' FSL &amp; 2014' FWL Section 25, T21S, R24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3649.4 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 0372996

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Indian Hills

9. WELL NO.

2-Y

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., E., M., OR BLK. AND  
SURVEY OR AREA

Sec. 25, T21S, R24E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) cementing surface casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/12/74 Ran 7 jts. 13 3/8" used casing, 202.41' less 11.21' cut off, landed 3' below KDB at 194.20' (using top part as flow nipple, to be cut off again before running 9 5/8" casing). Cemented with 210 sx Class "C" 2% CaCl<sub>2</sub>, 3# Gilsonite per sack, 1/8" celloflake per sack. Plug down at 5:30 p.m. 9/12/74. Cement circulated to cellar. Used one guide shoe, float insert, one centralizer on bottom joint. Left 31' cement in pipe (set 4' off bottom, could not wash down.)

RECEIVED

SEP 16 1974

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

9/13/74

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

SEP 16 1974

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side