

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to develop a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐ **JUL 01 1983**
2. NAME OF OPERATOR
Harvey E. Yates Company ✓ **O. C. D.**
3. ADDRESS OF OPERATOR **ARTESIA, OFFICE**
P. O. Box 1933, Roswell, New Mexico 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Treating & Remedial Work

SUBSEQUENT REPORT

- ☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

MAY 27 1983

OIL & GAS

ROSWELL, NEW MEXICO

5. LEASE
NM-03677
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Yates Federal "A" *Red*
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Burton Flats
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 21, T-20S, R-29E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3271' G

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 5/14/83 Pull 20 stands of 2 3/8" tbg. RU Geo Vann & run GRNL & CBL from 6000'-6310'. RD Geo Vann, RIH w/30 stands of 2 3/8" tbg to 7009'.
- 5/19/83 Pull tbg 00H, RU Carbon oxygen log from 6000'-5250'.
- 5/20/83 RIH w/tbg open-ended to 11009'.
- 5/24/83 RU Howco, brk circ, spot 60 sx, plug @ 9500' w/class "C" Neat. New PBTD 6300'. Perf: 5602', 5592', 5584', 5569', 5544', 5487', 5474', 5456', 5286', (9 holes, 1 spf). RIH w/4-1/2" Model R pkr, SN & 2 3/8" tbg to 5000'.
- 5/25/83 RIH w/2-3/8" tbg to 5611'. RU Howco & spot 250 gal 15% MSR acid. Pulled tbg & pkr to 5180' & set.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Ray T. [Signature]* TITLE Reservoir Engineer DATE May 26, 1983

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY **PETER W. CHESTER**
CONDITIONS OF APPROVAL, IF ANY:

JUN 29 1983

TITLE _____ DATE _____