

DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPER OR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

MAY 2 1975

O. C. C.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Cities Service Oil Company ✓		5. State Oil & Gas Lease No.
3. Address of Operator Box 1919 - Midland, Texas 79701		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>H</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>21S</u> RANGE <u>27E</u> NMPM.		8. Farm or Lease Name Tracy C Com.
		9. Well No. 1
		10. Field and Pool, or Wildcat Undesignated Morrow
15. Elevation (Show whether DF, RT, GP, etc.) 3150' GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of any proposed work) SEE RULE 1103.

T.D. 11,725' Shale. We propose to plug and abandon this well in the following manner:

1. Spot a 40 sack cement plug across top of Morrow (11046') @ approx. 11,100' - 11,000'.
2. Spot a 40 sack cement plug across top of Strawn (10050') @ approx. 10,100' - 10,000'.
3. Spot a 40 sack cement plug across top of Canyon (9398') @ approx. 9,450' - 9,350'.
4. Spot a 40 sack cement plug across top of Wolfcamp (8724') @ approx. 8,775' - 8,675'.
5. Spot a 40 sack cement plug across top of 2nd. Bone Springs Sand (7050') @ approx. 7,100 - 7,000'.
6. Spot a 40 sack cement plug across top of 1st. Bone Springs Sand (6290') @ approx. 6,350' - 6,250'.
7. Spot a 40 sack cement plug across top of Bone Springs (5078') @ approx. 5,125' - 5,025'.
8. Spot a 40 sack cement plug  $\frac{1}{2}$  in and  $\frac{1}{2}$  out of 9-5/8" csg. shoe (3003') @ approx. 3,050' - 2,950'.
9. Spot a 10 sack cement surface plug in top of 9-5/8" csg. @ approx. 58' - 0' with a 4" dry hole marker to designate a plugged and abandoned well.
10. Location will be cleared of all debris and equipment.

The above plugging prognosis approved verbally by Mr. W. A. Gressett, N.M.O.C.C. at Artesia, New Mexico on 4-23-75.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. P. Pugh TITLE Region Operation Manager April 30, 1975

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAY 2 1975

CONDITIONS OF APPROVAL, IF ANY: