

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0112134 - B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

MONSANTO COMPANY - PRODUCTION DEPT.✓

3. ADDRESS OF OPERATOR

321 West Texas, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 2310' FWL

RECEIVED

DEC 27 1974

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3544 Gr.

O. C. C.

ARTESIA, OFFICE

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T-21S, R-25E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17½" hole 5:00 PM 12/10/74.

Drilled 17½" hole to 400' & set 13 3/8" 48# H-40 ST&C casing @ 400'; Cemented w/ 300 Sx. Lite Wt + 150 Sx. Class "C"; Plug down 11:30 AM 12/13/74; Cmt did not circulate. Ran 1" in annulus and cemented thru 1" to surface w/ 415 Sx. Reg. Cement.

WOC 24 Hrs & tested w/ 1000 psi for 30 Mins., Held OK.

Drilled 12¼" hole to 2450' and set 9 5/8" 36# K-55 LT&C casing at 2450'; cemented to surface w/ 1000 Sx. Lite Wt + 150 Sx. Class "C" cement; Plug down 4:15 AM 12/20/74. WOC 24 Hrs. & tested w/ 1500 psi for 30 Mins., held OK.

RECEIVED

DEC 28 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Prod. Mgr.

DATE 12/24/74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DEC 26 1974
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side