

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 029588

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harris "6"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Golden Lane Field *1 to 2*

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-21S-29E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Meadco Properties LTD

3. ADDRESS OF OPERATOR

P. O. Box 2236, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

3147' FNL & 660' FEL, Sec. 6, T-21-S, R-29-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, ET, GR, etc.)

3469.6 Gr

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug & abandon the well bore because of parted casing at 2170'. Attempts to repair the 4 1/2" casing were unsuccessful and indicated that the 8 5/8" casing might also be parted.

Prognosis

- 1) Set 8 5/8 cmt retainer @ 2000'
- 2) Squeeze below retainer w/200 sx Class C Cmt
- 3) Unstring & leave 35' cmt on retainer
- 4) Spot 100' plug from 667' to 567'
- 5) Spot plug at surface.

Note: Approved verbally by Armando Lopez 7/18/83

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE: David Cotner - Engineer

DATE 8/30/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

[Signature]

SEP 1 1983

*See Instructions on Reverse Side

RECEIVED

AUG 31 1 03 PM '83

RECEIVED