

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

APR 9 1975

O. C. C.

10. Indicate Type of Lease State ☒ Free ☐
5. State Oil & Gas Lease No. E 5232
7. Unit Agreement Name Big Eddy Unit
8. Farm or Lease Name Big Eddy
9. Well No. 42
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REEVE, OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☐ GAS WELL ☐ OTHER - Dry Hole
2. Name of Operator Perry R. Bass
3. Address of Operator Box 2760, Midland, Texas 79701
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1900 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 21S RANGE 29E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3314' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Confirming telephone conversation March 20, 1975 - Mr. Raley to Mr. Gressett.

Propose to set plugs as follows:

100 sks Class H from 13,000' - 12,700'.
75 sks Class H from 12,100' - 11,900'.
40 sks Class H from 11,530' - 11,630'.
45 sks Class H from 10,960' - 11,060'.
50 sks Class H from 9,970' - 10,070'.
50 sks plain cement 8,450' - 8,550'.
40 sks plain cement from 6,638' - 6,738'.
40 sks plain cement from 2,970' - 3,070'.

Intervals between plugs to be filled with 10.1 #/gal salt-gel mud.

Surface plug and marker to be set after rig is moved.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED George A. Lee TITLE Staff Petroleum Engineer DATE April 7, 1975

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE APR 10 1975

CONDITIONS OF APPROVAL, IF ANY:

COUNTY	EDDY	FIELD	Wildcat	STATE	NM
OPR	BASS, PERRY R.			API	30-015-21455
NO	42	LEASE	Big Eddy Unit	SERIAL	4-3-4 NM
	Sec 32, T-21-S, R-29-E			MAP	
	660' FNL, 1980' FWL of Sec			CO-ORD	
	12 mi E/Carlsbad			ELEV	LBS
SPD	1-23-75	CMP	3-24-75	WELL CLASS:	INIT. WF FIN WF
CSG				FORMATION	DATUM
	13 3/8" at 401' w/525 sx				
	8 5/8" at 3019' w/1150 sx				
				TD 13,075 (MSSP)	PBD

DRY & ABANDONED

CONTR Mcvay OPR'S ELEV 3314' GL, 3331' KB^{PD} 13,500' RT

F.R. 1-13-75
(Morrow)

1-27-75 Drlg 2447' anhy & salt
Lost Circ @ 190'

2-3-75 Drlg 5895' lm & sd

2-10-75 Drlg 8901' lm & sh

2-18-75 Drlg 10,472' lm, sh & sd

2-25-75 Drlg 11,812' lm & sh

3-4-75 Drlg 12,620' lm, sh & cht
SAMPLE: Atoka Lime 11,870' (-8539')

3-10-75 TD 13,075'; Rng Logs

3-17-75 TD 13,075'; PBD 11,900'; Circ
Sidewall Cored @ 3141', 3144', 3188', 3190',

4-3-4 NM

EDDY
BASS, PERRY R.

Wildcat
#32 Big Eddy Unit
Sec 32, T21S, R29E

NM
Page #2

3-17-75
(Cont.)

3197', 3239', 3244', 3418', 3433', 3652',
3664', 3671', 3850', 3935', 3994', 4003',
4016', 4024', 4026', 4028', 4043', 4047',
4049', 4063', 4074', 4229', 4231', 4236',
4238'
DST 12,796-13,075', open 8 hrs 30 mins,
(2000' WB) G&WTS in 2 mins, Flwd 1111 MCFGPD
+ 18½ BWPB thru 20/64" chk; SFP 1200#, incr
1257 MCFGPD + 20 BWPB, SFP 1000#, rev out 35
BW + ½ B Cond, 1 hr 15 min ISIP 4086#, FP
3071-2864#, 8 hr FSIP 4064#, HP 6725#
SP-DST Atoka @ 11,706'; Pkr Failed
SP-DST 12,788-868', open 3 hrs (1973' WB),

4-3-4 NM

3-17-75
(Cont.)

rec WB + 2487' GCM, 1 hr 30 min ISIP 6702#,
FP 1249-2169#, 5 hr FSIP 6702#
(Pressure Inconclusive)

3-25-75

TD 13,075'; D&A (Hold for Tops)
PB to 10,820'

DST 11,750-820', open 2 hrs 30 mins, rec
3250' GCM, 1 hr 30 min ISIP 5859#, FP 78-194#,
3 hr FSIP 6099#, HP 6092-6099#

4-14-75

TD 13,075'; Dry & Abandoned
LOG TOPS: Delaware Sand 3064', Cherry Canyon
4528', Brushy Canyon 5404', Bone Spring 6688',
Wolfcamp 10,005', Strawn 11,329', Lusk 11,498',
Atoka 11,616', Atoka Lime 11,872', Morrow
12,203'

4-19-75

COMPLETION ISSUED

4-3-4 NM