

(Morrow) Perfs 11,190-266 NO NEW POTENTIAL

CONTR OPRS LLEV 3200GL sub-s

F.R.C. 9-19-81 OWWO
PD 11,370 WO (Morrow)
(Orig. comp. 4-2-76 thru (Morrow) Perfs 11,256-266,
OTD 11,700, OPB 11,370)
9-14-81 TD 11,700; PBD 11,370; Complete
Perf (Morrow) 11,190-196 w/4 SPF
Natural
9-19-81 COMPLETION ISSUED

9-3-30 NM
IC 30-015-70411-81

COUNTY EDDY FIELD Burton Flat STATE NM
 OPR YATES DRILLING CO. API 30-015-21491
 NO 2 LEASE Avalon Federal MAP
Sec 18, T21S, R27E CO-ORD
1980 FSL, 1980 FEL of Sec 6-2-9 NM
2 mi N/Carlshad SPD 3-5-75 CMP 4-2-76

CSG	WELL CLASS: INIT D FIN DGLSE. CODE			
	FORMATION	DATUM	FORMATION	DATUM
13 3/8-600-685 sx				
9 5/8-2708-1250 sx				
5 1/2-11,628-750 sx				
2 7/8-11,218				
	ID 11,700 (MSSP)	PBD	11,370	

IP (Morrow) Perf# 11,256-266 CAOF 5326 MCFGPD. GOR 422; gty
 (Gas) .580; (Cond) (NR); SIWHP (NR); SIBHP 3115

P.L.C. Transwestern Pipeline Co.

CONTR Arm OPRSELEV 3200 GL, 3214 KB sub-s 13

F.R. 2-24-75
 PD 11,700 RT (Morrow)
 3-17-75 AMEND FIELD: Formerly reported as Wildcat
 3-10-75 Drlg 1675
 Lost Circ @ 1234
 3-19-75 Drlg 4360
 DST (Delaware) 3737-3887, op 2 hrs, rec 25 FT OIL
 + 576 FT SGCW, 1 hr 30 min ISIP 508, FP 348-348,
 4 hr FSIP 654, HP 1684-1703, BHT 92 deg
 3-26-75 Drlg 6395
 4-1-75 Drlg 8275 1m
 4-9-75 Drlg 9950
 DST (Wolfcamp) 9022-9220, op 1 hr 45 mins, GTS in
 36 mins, rec 60 FT OIL + 360 FT GCM, 1 hr 30 min
 ISIP 1724, FP 71-106, 3 hr FSIP 3314, HP 4447-4447,
 BHT 148 deg
 DST (Wolfcamp) 9832-9945, op 2 hrs 7 mins, No
 recovery reported, 2 hr 43 min ISIP 5141, FP
 6-2-9 NM

EDDY
YATES DRILLING CO.

Burton Flat
2 Avalon Federal
Sec 18, T21S, R27E

NM
Page #2

4-9-75 Continued
186-256, 4 hr 30 min FSIP 5005
4-16-75 TD 10,907 sh, 1m & cht; Trip
4-24-75 Drlg 11,531; "Tight"
DST (Morrow) 11,017-347, op 1 hr 40 mins,
(1000 FT WTR CUSH), GTS 7 mins, MTS 8 mins,
chk plugged re-opened on second flow. No
gauges, rec 90 FT DFLUD + 135 FT WTR, 1 hr ISIP
4788, FP 3061-3610, 3 hr FSIP 4746, HP 5705-
5663, BHT 170 deg
5-1-75 TD 11,700; "Tight"
5-7-75 TD 11,700; WOCU
5-21-75 TD 11,700; PBD 11,628; Completing "Tight"

6-2-9 NM

5-28-75 TD 11,700; PBD 11,628; WO Pot
6-2-75 TD 11,700; PBD 11,370; WO Pot
Perf (Morrow) 11,392-396, 11,406-408, 11,409-
412, 11,446-456 w/4 SPF
Acid (11,392-396) 1000 gals
Non Commercial (11,392-456)
PB to 11,370
Perf (Morrow) 11,256-266 w/4 SPF
Natural
6-9-75 TD 11,700; PBD 11,370; Complete
(Morrow) FOUR POINT GAUGES:
Flwd 642 MCFGPD, chk NR, 60 mins, TP 1948
Flwd 925 MCFGPD, chk NR, 60 mins, TP 1749
Flwd 1343 MCFGPD, chk NR, 60 mins, TP 1685
Flwd 2422 MCFGPD, chk NR, 60 mins, TP 1492
LOG TOPS: Delaware Sand 2582, Bone Spring 4884,
6-2-9 NM