Form 9-331		• •				37
(May 1963)		TED STATES	C. C. C. C. C. C. DAY		Copy te	- ,
	DEPART	MENT OF THE IN	SUBMIT IN T	RI ICATE	Form approve	ed.
	6		IERIOR verse side)	tions on re-	Budget Bures D. LEASE DESIGNATION	AND SERVAY
		EOLOGICAL SURVE			NM 0400512	
SU	NDRY NOTI	CES AND REPOR	TS ON WELLS	6	IF INDIAN, ALLOTTER	-A
(Do not use th	is form for propos:	als to drill or to deepen or	plug tack to a different resuch proposals.)		,	OA TRIBE NAS
1.		TION FOR PERMIT-" for	such proposals.)			
OIL GAS WELL WELL	X OTHER	,		7.	UNIT AGREEMENT NAL	
2. NAME OF OPERATOR	LAJ OTHER	· · · · · · · · · · · · · · · · · · ·	<u>APR 9 19</u>	75		~ 2
	MONGANING	6 00 m (see)			FARM OR LEASE NAME	
3. ADDRESS OF OPERAT	MONSANTO	COMPANY				
		Town Will 1	ARTESIA, OFFIC	9.	COQUINA - FEI	DERAL
4. LOCATION OF WELL (Report location als	Texas, Midland,	Texas 79701	·E	1	
See also space 17 be At surface	low.)	arly and in accordance with	any State requirements.*	10	. FIELD AND POOL, OR	NUMBER OF COMPANY
1980	FFI and 10					
		80' FSL of Secti	on 31	11	Undesignated	1
					SUEVEY OR AREA	A. AND
14. PERMIT NO.					Sec. 31, T-20	תרכם סו
		15. ELEVATIONS (Show wheth	er DF, RT, GR, etc.)		COUNTY OR PARISH	5, K-2/E
		DF 3242; Gr. 3			Eddy	
16.	Check App	ropriate Roy To India	ha Nilata (hit	<u> </u>	Dady	New Mex
	NOTICE OF INTENTIO	a more box to indicd	te Nature of Notice, Re	port, or Other	r Data	
	F			SUBSEQUENT		
TEST WATER SHUT-O	PUI PUI	LL OR ALTER CASING	WATER SHUT-OFF	·····		·
FRACTURE TREAT	MU:	LTIPLE COMPLETE	FRACTURE TREAT	(REPAIRING WE	
SHOOT OR ACIDIZE	ABA	NDON*	SHOOTING OR ACI	[·]	ALTERING CASI	J1
REPAIR WELL	Сну	NGE PLANS	(Other)Sp		ABANDONMENT*	' <u> </u>
(Other)			(37.		ultiple completion on Report and	
		30 PM 3/25/75.	inent details, and give perti- locations and measured and	rue vertical dep	ths for all markers ar	id zones perti
Spudded 17눌" Drilled 17눌"	hole at 9:	30 PM 3/25/75.		•		· .
Spudded 17눌" Drilled 17눌"	hole at 9:	30 PM 3/25/75.		•		· .
Spudded 17날" Drilled 17날" Cemented to	hole at 9: hole to to surface w/	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt	' and set 13 3/8' & 150 Sx. Class '	•		· .
Spudded 17날" Drilled 17날" Cemented to	hole at 9: hole to to surface w/	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt	' and set 13 3/8' & 150 Sx. Class '	•		· .
Spudded 17날" Drilled 17날" Cemented to WOC 24 Hrs. d	hole at 9: hole to to surface w/ & tested w/	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK.	' 54.5# K- 'C"; Plug d	55 ST&C Csg a down @ 2:30 P	t 500'; M 3/27/7
Spudded 17날" Drilled 17날" Cemented to WOC 24 Hrs. 6 Drilled 12날"	hole at 9: hole to to surface w/ & tested w/	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK.	' 54.5# K-! 'C''; Plug d	55 ST&C Csg a down @ 2:30 P	t 500'; M 3/27/7
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. 0' and set 9 5/8"	' 54.5# K- 'C''; Plug d 36# K-55	55 ST&C Csg a down @ 2:30 P	t 500'; M 3/27/7
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to s "C", 2% CaCl held OK.	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75;	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75;	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	' 54.5# K- 'C''; Plug d '36# K-55 # Flocele/	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080'
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to s "C", 2% CaCl held OK.	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75;	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	54.5# K-2 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P. LT&C Csg set (Sx. + 150 Sx 00 psi for 30 LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. 6 Drilled 12½" Cemented to 3 "C", 2% CaCl held OK.	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22. TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, 2	54.5# K-1 C"; Plug of 36# K-55 # Flocele/ ted w/ 150	55 ST&C Csg a down @ 2:30 P LT&C Csg set 'Sx. + 150 Sx	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to s "C", 2% CaCl held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22. TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	54.5# K-1 C"; Plug of 36# K-55 # Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P. LT&C Csg set (Sx. + 150 Sx 00 psi for 30 LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. & Drilled 12½" Cemented to s "C", 2% CaCl held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22 TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	54.5# K-1 C"; Plug of 36# K-55 # Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P. LT&C Csg set (Sx. + 150 Sx 00 psi for 30 LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. d Drilled 12½" Cemented to s "C", 2% CaCl held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22. TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	' 54.5# K-9 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150 Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P. LT&C Csg set (Sx. + 150 Sx 00 psi for 30 LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON CR 00 CSCAL NEARON	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. & Drilled 12½" Cemented to s "C", 2% CaC1 held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22 TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	' 54.5# K-9 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150 Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CATE 4/3/75	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. & Drilled 12½" Cemented to s "C", 2% CaC1 held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22 TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	' 54.5# K-9 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150 Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CATE 4/3/75	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. & Drilled 12½" Cemented to s "C", 2% CaC1 held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22 TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	' 54.5# K-9 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150 Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CINER SUME OF A 1975 CEOLOGICAL MENTO OF A 1975 CEOLOGICAL ME	t 500'; M 3/27/7 @ 2080' . Class Mins.,
Spudded 17½" Drilled 17½" Cemented to WOC 24 Hrs. & Drilled 12½" Cemented to s "C", 2% CaC1 held OK. 18. I hereby certify that th SIGNED	hole at 9: hole to to surface w/ & tested w/ hole to to surface w/ 8 ; Plug down	30 PM 3/25/75. tal depth of 500 450 Sx. Lite Wt 1000 psi for 30 tal depth of 208 800 Sx. Lite Wt. 6:00 AM 4/2/75; and correct 22 TITLE	' and set 13 3/8' & 150 Sx. Class ' Mins., held OK. O' and set 9 5/8" , 5# Gilsonite, ½ WOC 24 Hrs & tes	' 54.5# K-9 'C''; Plug of '36# K-55 # Flocele/ ted w/ 150 Flocele/ ted w/ 150	LT&C Csg set down @ 2:30 P LT&C Csg set (Sx. + 150 Sx 00 psi for 30 CINER SUME OF A 1975 CEOLOGICAL MENTO OF A 1975 CEOLOGICAL ME	t 500'; M 3/27/7 @ 2080' . Class Mins.,