

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUL 2 1975

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 1M X 1171	
7. Unit Agreement Name Livingston Ridge Unit	
8. Farm or Lease Name Livingston Ridge Unit	
9. Well No. 1-Y	
10. Field and Pool, or Wildcat Undes. Cabin Lake Morrow	
12. County Eddy	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK OR TO RE-ENTER A WELL. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

O.C.C.
ARTESIA OFFICE

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator Corinne Grace	
3. Address of Operator P. O. Box 1418, Carlsbad, New Mexico 88220	
4. Location of Well UNIT LETTER L, 1980, South LINE AND 990 FEET FROM THE West LINE, SECTION 36, TOWNSHIP 21S, RANGE 30E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3238.7	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 7" 32# & 29# liner from 7379 to 13780 with 199' overlap in 9 5/8" casing. Mixed 1320 sks class "H" cement with 1% CER-2 slurry wt 15.6 slurry volume 1297 cu.ft. Displaced cement in 7" liner w/137 bbl of 10.1 brine water. Plug down 6 a.m. WOC 24 hours Pressured up to 1500 - o.k.

Guide shoe	1.78
7" csg. 32#	40.87
Float Collar	1.41
Landing Collar	.83
76 jts. 32# csg.	3058.77
82 jts. 29# csg.	3284.91
csg. hanger	5.30
tie back sleeve	7.17
	<u>6401.04</u>

Cement was circulated above 7" liner.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Wanda R. Jones TITLE Agent DATE 6/18/75

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE JUL 9 1975

CONDITIONS OF APPROVAL, IF ANY: