

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>12,194</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>12,409</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand <u>3750</u>	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs <u>7552</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>10720</u>	T. Morrow <u>13022</u>	T. Chinle _____	T. _____
T. Penn. _____	T. Barnett <u>13723</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	270	270	Surface beds				
270	610	340	Anhydrite, Dolomite & lime				
610	3700	3090	Salt & anhy.	13620	13730	110	Sand & Shale
3700	3830	130	Limestone	13730	13770	40	Shale & Sand
3830	3880	50	Sand & lime				
3880	4390	510	Sand				
4390	4880	490	Sand & lime				
4880	7560	2680	Sand & Shale				
7560	8160	600	Lime & Shale				
8160	8340	180	Shale & lime				
8340	8510	170	Lime				
8510	9075	565	Sand, Lime & Shale				
9075	9210	135	Lime				
9210	9610	400	Sand & Lime				
9610	9800	190	Lime				
9800	10320	520	Lime & Shale				
10320	10940	620	Sand Lime Shale				
10940	11350	410	Lime & Shale				
11350	11410	60	Sand Lime & Shale				
11410	12100	690	Shale & Lime				
12100	12610	510	Lime & Shale				
12610	12690	80	Sand Shale & Lime				
12690	12800	110	Lime & Shale				
12800	13150	350	Shale Lime & Sand				
13150	13200	50	Lime				
13200	13290	90	Shale				
13290	13480	190	Sand Shale Coal				
13480	13620	140	Shale & Sand				