

UN ID STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side)FE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 050797

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government AC Com.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undes. Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 13-T20S-R28E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Cities Service Oil Company ✓

MAY 15 1975

3. ADDRESS OF OPERATOR

Box 1919 - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

ARTESIA, OFFICE

1800'FNL & 1980'FWL of Sec. 13-T20S-R28E, Eddy Co., New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3255' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 900' Anhydrite. Prep to drill ahead. This well was spudded @ 1:00 AM on 5-9-75 and drilled to a T.D. of 900'. Ran 25 Jts. (884.50') 13-3/8" OD 48# H-40 casing set and cemented @ 900' w/475 sacks Halliburton Lite w/1/4# Flocele and 5# Gilsonite/sack followed by 300 sacks Class C w/2% CaCl cement. Plug down @ 2:20 AM on 5-12-75. Bumped float w/900# - Held O.K. Cement circulated to surface. WOC 18 hrs. Tested 13-3/8" casing to 750# for 30 minutes with no drop in pressure.

U.S.G.S. was notified but did not witness cementing job.

RECEIVED
MAY 14 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

DATE May 13, 1975

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side